

S60-T PORTABLE PAYMENT TERMINAL

- 🔒 PCI PTS certified
- 🔒 Innovative and portable design
- 🔒 Designed for pay-at-the-table service
- 🔒 MasterCard Contactless, Visa payWave



PAX's S60-T is a unique device featuring a compact, ruggedized and yet lightweight POS terminal into a docking station with communications and high-speed thermal printer (or optional sprocket printer).

Equipped with a built-in secure PINPad, PCI PTS certified, the portable handset provides a secure and convenient payment experience for merchants and cardholders. With 4 ATM style keys, the S60-T streamlines payments and enhances the customer experience, offering ease of use for both merchant and consumers.

The S60-T is designed for payments at the point of service, such as restaurant and hotel environments, making it a powerful solution for a variety of business applications.

S60-T PORTABLE PAYMENT TERMINAL

SPECIFICATIONS

Handset Unit

Processor

32-bit ARM11

Memory

192MB (128MB Flash, 64MB DDR)

Display

128 pixel x 64 pixel LCD, White backlit

Keypad

10 numeric keys & 8 function keys
4 ATM keys, 1 power ON / OFF key

Magnetic Card Reader

Track 1 / 2 / 3, bi-directional

Smart Card Reader

1 user card, EMV 2000

Contactless Card Reader (optional)

MasterCard Contactless & Visa payWave
ISO14443 Type A/B, Mifare®, Felica
Maximum effective distance up to 4cm

Card Slots

3 SAM Slots, ISO7816

Communication

Infrared communication port

Peripheral Port

1 x mini USB

Battery

Li-ion battery, 750mAh

Security

DUKPT, Master / Session, 3DES
ANSI / ISO9564 format 0, 1, 3
PIN ciphered key algorithm
ANSI X9.9 / X9.19 MAC algorithm

Environmental

0°C to 50°C (32°F to 122°F) operating temperature
10% to 93% relative humidity, non-condensing
-20°C to 70°C (-4°F to 158°F) storage temperature

Physical

Length: 165mm
Width: 84mm
Height: 35mm

Weight

302g

Base Unit

Processor

32-bit ARM 9

Memory

12MB

Printer

Thermal graphic printer, Speed: 20 lines / second
Standard paper roll: 58mm (diameter: 50mm)

Peripheral Ports

2 x RS232, 1 x PINPad, 1 x Line,
1 x Ethernet (optional)

Communication

Modem:
Sync. (HDL, up to 9600bps)
Async. (V.92, up to 56Kbps)
Ethernet (optional)

Environmental

0°C to 50°C (32°F to 122°F) operating temperature
10% to 93% relative humidity, non-condensing
-20°C to 70°C (-4°F to 158°F) storage temperature

Voltage

Input: 100~240VAC, 50Hz / 60Hz, 0.8A
Output: 8.2VDC, 2.5A

Physical (with paper holder)

Length: 230mm
Width: 104mm
Height: 86mm

Weight

680g

Certifications

PCI PTS
MasterCard Contactless
Visa payWave
EMV
PBOC
qPBOC

FEATURES

- Large Memory Capacity
- Optional built-in contactless card reader
- Fast thermal printer
- Multiple connectivity options - Ethernet & Dial
- Ideal with hospitality merchants



Corporate Headquarters

4/F, No.3 Building, Software Park,
2nd Central Science-Tech Road,
High-Tech Industrial Park,
Shenzhen 518057,
P.R. C.
T: +86 755 8616 9630
F: +86 755 8616 9634
E: market@paxsz.com

North America

4901 Belfort Road
Suite 130,
Jacksonville,
FL 32256,
USA
T: +1 904 900 3741
E: inquiry@pax.us

Asia Pacific

Room 2416, 24/F.,
Sun Hung Kai Centre,
30 Harbour Road,
Wanchai,
Hong Kong
T: +852 2500 8500
F: +852 2598 0299

EMEA Region

Portland House
16th Floor
Bressenden Place
London SW1E 5RS
United Kingdom
T: +44 (0)208 433 6570
F: +44 (0)207 869 8001
E: EMEA@paxsz.com

LACIS Region

4/F, No.3 Building, Software Park,
2nd Central Science-Tech Road,
High-Tech Industrial Park,
Shenzhen 518057,
P.R. C.
T: +86 755 8616 9630
F: +86 755 8616 9634
E: LACIS@paxsz.com

THIS DOCUMENT IS PROVIDED TO YOU FOR INFORMATIONAL PURPOSES ONLY. ALL FEATURES AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

PAX are either trademarks or registered trademarks of PAX Technology Limited in China and/or other countries. All other trademarks or brand names are the properties of their respective holders. Copyright 2012, PAX Technology Limited. All Rights Reserved.