S78 COUNTERTOP PAYMENT TERMINAL

PCI PTS approved

- Sprocket printer enabled
- Compact and sleek design



PAX's S78 is a unique sprocket printer enabled POS terminal, offering all the performance and security of traditional countertop devices, to merchants with special receipt or voucher printing requirements.

With a powerful 32-bit ARM11 processor, the S78 is ideally suited to both EMV and value-added transactions.

The S78 can be readily adapted to a variety of merchant environments, given the many connectivity options, and the many peripheral ports available.

www.pax.com.cn

S78 COUNTERTOP PAYMENT TERMINAL

SPECIFICATIONS

Processor 32-bit ARM11

Memory 192MB (128MB Flash, 64MB DDR)

Display 128 pixel x 64 pixel LCD, White backlit

Keypad 10 numeric & 9 function keys 1 Power ON / OFF key

Printer Sprocket printer, Speed: 4 lines / second Standard paper width: 76mm

Magnetic Card Reader Track 1 / 2 / 3, bi-directional

Smart Card Reader 1 user card, EMV 2000

Card Slots 4 SAM Slots ISO 7816

Communication

Modem: Sync. (HDLC, up to 9600bps) Async. (V.92, up to 56Kbps) Ethernet

Peripheral Ports 2 x RS232, 1 x PINPad, 1 x Ethernet 1 x Line, 1 x TEL, 1 x mini USB

Security DUKPT, Master / Session, DES, 3DES ANSI / ISO9564 format 0, 1, 3 PIN ciphered key algorithm ANSI X9.9 / X9.19 MAC algorithm

Environmental

0°C to 50°C (32°F to 120°F) operating temperature 10% to 93% relative humidity, non-condensing -20°C to 70°C (-4°F to 150°F) storage temperature

Voltage Input: 100-240VAC, 50Hz / 60Hz, 1.5A Output: 24VDC, 1.8A

Physical Length: 315mm

FEATURES

- Large memory capacity
- EMV & PCI compliant
- USB connectivity
- Supports multiple applications





Corporate Headquarters

4/F, No.3 Building, Software Park, 2nd Central Science-Tech Road, High-Tech Industrial Park, Shenzhen 518057, P.R. C. T: +86 755 8616 9630

F: +86 755 8616 9634 E: market@paxsz.com

North America

4901 Belfort Road Suite 130, Jacksonville. FL 32256, USA T· +1 904 900 3741 E: inquiry@pax.us Asia Pacific

Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Road, Wanchai, Hong Kong T: +852 2500 8500 F: +852 2598 0299

EMEA Region

Portland House 16th Floor Bressenden Place London SW1E 5RS United Kingdom T: +44 (0)208 433 6570 F: +44 (0)207 869 8001 E: EMEA@paxsz.com

LACIS Region

4/F, No.3 Building, Software Park, 2nd Central Science-Tech Road, High-Tech Industrial Park, Shenzhen 518057, P.R. C T: +86 755 8616 9630 F: +86 755 8616 9634 E: LACIS@paxsz.com

THIS DOCUMENT IS PROVIDED TO YOU FOR INFORMATIONAL PURPOSES ONLY. ALL FEATURES AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE PAX are either trademarks or registered trademarks of PAX Technology Limited in China and/or other countries. All other trademarks or brand names are the properties of their respective holders. Copyright 2012, PAX Technology Limited, All Rights Reserved.

Width: 153mm Height: 126mm

Weight 1300g

Certifications

PCI PTS EMV L1 & L2 PBOC